TABLE OF CONTENTS

| | | Page N |
|--------|---|--------|
| СНАРТЕ | ER 1 TURE HECHANISM OF FIRRE CONCRETE | |
| 1.1 | INTRODUCTION | 17 |
| | | |
| CHAPTE | CR 2 INTRODUCTION TO FIBRE REINFORCED CONCRETE | |
| <2.1 | INTRODUCTION | 5 |
| 2.2 | REINFORCED CONCRETE | 6 |
| , , | 2.2 a Reinforced Concrete | 6 |
| | 2.2 b Prestressed Concrete | 6 |
| | 2.2 c Micro reinforcement | 7 |
| /2.3 | PROPERTIES OF FIBRE REINFORCED CONCRETE | 8 |
| | 2.3 a Fibre reinforced concrete with fibre of low | |
| | modulus of elasticity | 8 |
| | 2.3 b Fibre reinforced concrete with fibres of high | |
| | modulus of elasticity | 9 |
| 2.4 | TYPE OF FIBRE | 9 |
| | 2.4 a Asbestos fibre | 9 |
| | 2.4 b Carbon fibre | 10 |
| | 2.4 c Steel fibre | 10 |
| | 2.4 d Glass fibres | 10 |
| 2.5 | FACTORS AFFECTING THE STRENGTH OF FIBRE REINFORCED CONCRETE | 13 |
| | 2.5.1 Fibre orientation | 13 |
| | 2.5.2 Fibre matrix interfacial bond | 13 |
| | 2.5.3 Fibre volume fraction | 15 |
| | 2.5.4 Fibre dispersion and quality control | 16 |
| | 2.5.6 Vibration of fibrous composites | 16 |

| | | Page No |
|--------|---|---------|
| 12.6 | FAILURE MECHANISM OF FIBRE CONCRETE | 16 |
| | 2.6.1 Crack arrest mechanism (spacing concept) | 17 |
| | 2.6.2 The composite approach two phase composite | 18 |
| 2.7 | PRODUCTION | 19 |
| | 2.7.1 Methods of production | 19 |
| | 2.7.2 Curing | 23 |
| | 2.7.3 Quality control | 23 |
| | 2.7.3a Green state | 23 |
| | 2.7.3b Long term assessment | 23 |
| | 2.7.3c Prototype testing | 24 |
| 2.8 | POLYPROPYLENE FIBRE COMPOSITES | 24 |
| СНАРТЕ | ER 3 THEORETICAL BEHAVIOUR OF FIBRE REINFORCED CONCRETE | |
| 3.1 | INTRODUCTION | 33 |
| 3.2 | COMPOSITE HAVING LONG ALIGNED FIBRE | 35 |
| 3.3 | TENSILE STRESS-STRAIN CURVE FOR BONDED FIBRE COMPOSITE | 40 |
| 3.4 | THE STRAIN ENHANCEMENT (Bonded Case) | 41 |
| 3.5 | BONDED UNBONDED CASE | 42 |
| 3.6 | EFFICIENCY OF FIBRE RANDOMNESS | 42 |
| 3.7 | SHORT FIBRE REINFORCED COMPOSITE | 44 |
| | 3.7a Aligned fibre | 44 |
| | 3.7b Random short fibrous composite | 46 |
| V3.8 | THEORETICAL FLEXURAL BEHAVIOUR | 48 |
| 3.9 | CONCLUSION | 49 |

| | | | Page No |
|-------|-----------------------|---|---------|
| CHAPT | ER 4 E | QUIPMENT AND PROCESS DEVELOPMENT | |
| 4.1 | INTRODUCTION | | |
| 4.2 | PROCESS AND EQUIPMENT | | 58 |
| | 4.2a | The concrete spray system | 58 |
| 4.3 | THE MIX PROPORTIONS | | 61 |
| | 4.4.1 | Fibre cutting and dispensing | 62 |
| | 4.4.2 | The main problems encountered | 63 |
| | 4.5.1 | Spraying and compacting the fibre reinforced concrete | 65 |
| | 4.5.2 | Compaction. | 65 |
| | | | |
| CHAPT | | LYPROPYLENE FIBRE COMPOSITE MATERIAL INVESTIGATION TEST | |
| | PR | OGRAM, TEST METHOD, MATERIALS, RESULTS AND DISCUSSION | |
| | 5.1.1 | Scope | 72 |
| | 5.1.2 | The tests undertaken | 73 |
| | 5.1.3 | The test program | 74 |
| 5.2 | TEST P | ROCEDURE | 75 |
| | 5.2.1 | Bond strength | 75 |
| | 5.2.2 | Test 2 : Direct tensile test | 76 |
| | 5.2.3 | Test 3: Flexural properties | 78 |
| | 5.2.4 | Concrete crushing strength | 80 |
| | 5.2.5 | Specific gravity of concrete | 80 |
| | 5.2.6 | Determination of fibre content | 81 |
| 5.3 | TEST R | ESULTS AND ANALYSIS | 82 |
| | 5.3.1 | Flexural behaviour | 83 |
| | 5.3.1a | At 1st crack | 83 |
| | 5.3.2b | After 1st crack | 84 |
| | 5.3.1c | Toughness index and fibre content | 84 |
| | 5.3.2 | The composite behaviour under direct tension | 85 |

| | | Page No. |
|-------|---|----------|
| | 5.3.2a At 1st crack | 85 |
| | 5.3.2b After cracking | 86 |
| | 5.3.2c Toughness index in direct tension | 87 |
| 5.4 | EFFECT OF MATRIX FINENESS ON THE COMPOSITE | 88 |
| 5.5 | SPRAYED. NON VIBRATED COMPOSITES | 88 |
| 5.6 | CONCLUSIONS | 90 |
| | 5.6.1 Mixing tour at the | 90 |
| | 5.6.2 Compaction | 90 |
| | 5.6.3 Properties Improvement | 91 |
| | 5.6.4 Future work | 91 |
| | | |
| HAPTE | R 6 COMPARATIVE STUDY BETWEEN FIBRILLATED FIBRE COMPOSITE AND | |
| | FIBREMESH COMPOSITES | |
| | 6.1.1 Introduction | 161 |
| | 6.1.2 Material properties | 162 |
| 6.2 | TESTS AND TEST PROGRAM | 163 |
| | 6.2.1 Test program | 163 |
| | 6.2.2 Mixing | 163 |
| | 6.2.3 Test and test procedures | 164 |
| 6.3 | RESULTS ANALYSIS AND CONCLUSIONS | 166 |
| | 6.3.1 The composite compressive strength | 166 |
| | 6.3.2 Effect of fibre on compaction | 167 |
| | 6.3.3 Flexural properties of the composites | 167 |
| | 6.3.3a Prisms | 168 |
| | 6.3.3al The effect of fibre at 1st crack | 168 |
| | 6.3.3a2 Effect of fibre at ultimate | 168 |
| | 6.3.3b Slab specimens | 169 |
| | 6.3.3bl At 1st crack | 171 |
| | 6.3.3b2 After the 1st track | 171 |
| | 6.3.3c Effect of fibre on toughness index | 172 |
| 6.4 | CONCLUSIONS | 173 |

| | | Page no |
|--------|--|---------|
| CHAPTE | ER 7 ONE WAY SLABS | |
| | CONCLUSIONS | |
| 7.1 | TEST PROGRAM | 210 |
| 7.2 | TEST PROCEDURE - ONE WAY SLAB | 212 |
| 7.3 | RESULTS ANALYSIS AND DISCUSSION - ONE-WAY SLABS | 212 |
| | 7.3.1 The matrix compressive strength | 213 |
| | 7.3.2 Behaviour in flexure | 213 |
| | 7.3.2.1 Behaviour at 1st crack | 214 |
| | 7.3.2.2 Behaviour just after 1st crack | 214 |
| | 7.3.2.3 Behaviour after 1st crack | 215 |
| 7.4 | TOUGHNESS INDEX | 218 |
| 7.5 | COMPARISON BETWEEN SLABS TESTED FACE UP AND FACE DOWN | 218 |
| 7.6 | SPRAYED FIBRILLATEDFIBRE COMPOSITE VS. SPRAYED FIBREMESH | |
| | COMPOSITE | 220 |
| СНАРТЕ | ER 8 TWO-WAY SLABS | |
| 8.1 | TEST PROGRAM | 253 |
| 8.2 | TEST PROCEDURE | 254 |
| 8.3 | YIELD LINE ANALYSIS OF TWO-WAY SLABS | 255 |
| 8.4 | RESULTS AND DISCUSSION | 258 |
| | 8.4.1 Matrix compressive strength | 259 |
| | 8.4.2 Slab behaviour | 259 |
| | 8.4.2.1 Behaviour at 1st crack | 260 |
| | 8.4.2.2 Behaviour after 1st crack | 260 |
| | 8.4.2.3 Toughness | 262 |
| 8.5 | THEORETICAL VS. TEST LOAD OF TWO-WAY SLABS | 263 |
| 8.6 | TENSILE STRESS DEVELOPED AT ULTIMATE TWO WAY SLABS VS. | |
| | ONE-WAY SLABS | 265 |
| 8.7 | DRUABILITY OF THE COMPOSITE AND THE STRENGTH OF 90 DAY SPECIMEN | |
| | SLAB PERFORMANCE AS A STRUCTURAL ELEMENT | 272 |
| | The state of the s | 411 |

| | | | Page No. |
|---------|-----------------------------|--|----------|
| CHAPTER | 9 CONC | LUSIONS AND RECOMMENDED FUTURE WORK | |
| 9.1 | CONCLUS | SIONS | 305 |
| | 9.1.1. | Composite production | 305 |
| | 9.1.2 | Tests and test specimens | 307 |
| | 9.1.3 | Durability of the composite | 308 |
| | 9.1.4 | Fibre composite products and performance | 309 |
| 9.2 | 9.2 RECOMMENDED FUTURE WORK | | 310 |
| | 9.2.1 | Production of the composite | 310 |
| | 9.2.2 | Materials | 311 |
| | 9.2.3 | Trials for various prototype products | 312 |